

ODE-3-120043-1F1A-01

Optidrive E3 Single Phase VFD Datasheet

0.37 kW (0.5 HP), 4.3 A, 200-240 V, 1PH

IP66 Outdoor Non-switched Variable Frequency Drive
with EMC Filter



Input Ratings

Supply Voltage	200-240 V
Input Phases	1
Supply Current Continuous	6 A
Supply Fuse or MCB (Type B)	10 A

Output Ratings

Motor Output Rating	0.37 kW (0.5 HP)
Output Voltage	0 – Supply Voltage
Output Current	4.3 A

Cable Information

Max Supply Cable Size	8 mm ² (0.01 sq in)
Max Motor Cable Size	8 mm ² (0.01 sq in)
Max Motor Cable Length	100 m (328 ft)

Factory Build Options

EMC Filter	Internal EMC Filter
Brake Transistor	No Internal Brake Transistor
Enclosure	IP66 Outdoor Non-switched
Display	LED

Drive Dimensions

Size	1
Height	232 mm (9.13 in)
Width	161 mm (6.34 in)
Depth	152 mm (5.98 in)
Weight	2.3 kg (5.07 lbs)
Fixings	4 x M4

Packaged Dimensions

Height	205 mm (8.07 in)
Width	210 mm (8.27 in)
Depth	345 mm (13.58 in)
Weight	2.9 kg (6.39 lbs)



SHC24

Buy this drive or get more
information:

<https://www.shc-24.com>

 **Invertek**
Drives.com