

# ODE-3-120070-1F1A

## Optidrive E3 VFD Datasheet

### 1.5 kW (2 HP), 7 A, 200-240 V, 1-3PH

IP66 Outdoor Non-switched Variable Frequency Drive  
with EMC Filter



#### Input Ratings

|                             |           |
|-----------------------------|-----------|
| Supply Voltage              | 200-240 V |
| Input Phases                | 1         |
| Supply Current Continuous   | 12.9 A    |
| Supply Fuse or MCB (Type B) | 16 A      |

#### Output Ratings

|                     |                    |
|---------------------|--------------------|
| Motor Output Rating | 1.5 kW (2 HP)      |
| Output Voltage      | 0 – Supply Voltage |
| Output Current      | 7 A                |

#### Cable Information

|                        |                                |
|------------------------|--------------------------------|
| Max Supply Cable Size  | 8 mm <sup>2</sup> (0.01 sq in) |
| Max Motor Cable Size   | 8 mm <sup>2</sup> (0.01 sq in) |
| Max Motor Cable Length | 100 m (328 ft)                 |

#### Factory Build Options

|                  |                              |
|------------------|------------------------------|
| EMC Filter       | Internal EMC Filter          |
| Brake Transistor | No Internal Brake Transistor |
| Enclosure        | IP66 Outdoor Non-switched    |
| Display          | LED                          |



# SHC24

Buy this drive or get more  
information:

<https://www.shc-24.com>

#### Drive Dimensions

|         |                   |
|---------|-------------------|
| Size    | 1                 |
| Height  | 232 mm (9.13 in)  |
| Width   | 161 mm (6.34 in)  |
| Depth   | 152 mm (5.98 in)  |
| Weight  | 2.3 kg (5.07 lbs) |
| Fixings | 4 x M4            |

#### Packaged Dimensions

|        |                   |
|--------|-------------------|
| Height | 205 mm (8.07 in)  |
| Width  | 210 mm (8.27 in)  |
| Depth  | 345 mm (13.58 in) |
| Weight | 2.9 kg (6.39 lbs) |

 **Inverter**  
Drives.com