

ODP-2-84250-3KR4N-MN

Optidrive P2 VFD Datasheet

250 kW, 480 A, 380-480 V, 3PH

IP55 Variable Frequency Drive with TFT Display



Input Ratings

Supply Voltage	380-480 V
Input Phases	3
Supply Current Continuous	480 A
Supply Fuse or MCB (Type B)	600 A

Output Ratings

Motor Output Rating	250 kW (400 HP)
Output Voltage	0 – Supply Voltage
Output Current	480 A

Cable Information

Max Supply Cable Size	240 mm ² (0.37 sq in)
Max Motor Cable Size	240 mm ² (0.37 sq in)
Max Motor Cable Length	100 m (328 ft)

Factory Build Options

EMC Filter	High Performance EMC Filter
Brake Transistor	Internal
Enclosure	IP55
Display	TFT Display
PCB Coating	Standard

Drive Dimensions

Size	8
Height	1334 mm (52.52 in)
Width	444 mm (17.48 in)
Depth	423 mm (16.65 in)
Weight	144 kg (317.47 lbs)
Fixings	4 x M12

Packaged Dimensions

Height	980 mm (38.58 in)
Width	610 mm (24.02 in)
Depth	1040 mm (40.94 in)
Weight	165 kg (363.76 lbs)



SHC24

Buy this drive or get more
information:

<https://www.shc-24.com>

 **Invertetek**
Drives.com