

ODV-3-220105-1F1E-MN

Optidrive Eco VFD Datasheet

2.2 kW (3 HP), 10.5 A, 200-240 V, 1-3PH
IP66 With Disconnect Outdoor Variable Frequency
Drive with EMC Filter and TFT Display



Input Ratings

Supply Voltage	200-240 V
Input Phases	1
Supply Current Continuous	19.3 A
Supply Fuse or MCB (Type B)	25 A

Output Ratings

Motor Output Rating	2.2 kW (3 HP)
Output Voltage	0 – Supply Voltage
Output Current	10.5 A

Cable Information

Max Supply Cable Size	8 mm ² (0.01 sq in)
Max Motor Cable Size	8 mm ² (0.01 sq in)
Max Motor Cable Length	100 m (328 ft)

Factory Build Options

EMC Filter	Internal EMC
Brake Transistor	No Brake Transistor
Enclosure	IP66 With Disconnect Outdoor
Display	TFT Display
PCB Coating	Standard

Drive Dimensions

Size	2
Height	257 mm (10.12 in)
Width	188 mm (7.4 in)
Depth	182 mm (7.17 in)
Weight	3.5 kg (7.72 lbs)
Fixings	4 x M4

Packaged Dimensions

Height	215 mm (8.46 in)
Width	235 mm (9.25 in)
Depth	375 mm (14.76 in)
Weight	4.2 kg (9.26 lbs)



SHC24

Buy this drive or get more
information:
<https://www.shc-24.com>

Invertek
Drives.com