

ODV-3-260031-301A-MN

Optidrive Eco VFD Datasheet

1.5 kW (2 HP), 3.1 A, 500-600 V, 3PH

IP66 Non Switched Outdoor Variable Frequency Drive
with TFT Display



Input Ratings

Supply Voltage	500-600 V
Input Phases	3
Supply Current Continuous	3.7 A
Supply Fuse or MCB (Type B)	10 A

Output Ratings

Motor Output Rating	1.5 kW (2 HP)
Output Voltage	0 – Supply Voltage
Output Current	3.1 A

Cable Information

Max Supply Cable Size	8 mm ² (0.01 sq in)
Max Motor Cable Size	8 mm ² (0.01 sq in)
Max Motor Cable Length	100 m (328 ft)

Factory Build Options

EMC Filter	No Internal EMC
Brake Transistor	No Brake Transistor
Enclosure	IP66 Non Switched Outdoor
Display	TFT Display
PCB Coating	Standard

Drive Dimensions

Size	2
Height	257 mm (10.12 in)
Width	188 mm (7.4 in)
Depth	172 mm (6.77 in)
Weight	3.5 kg (7.72 lbs)
Fixings	4 x M4

Packaged Dimensions

Height	215 mm (8.46 in)
Width	235 mm (9.25 in)
Depth	375 mm (14.76 in)
Weight	4.2 kg (9.26 lbs)



SHC24

Buy this drive or get more
information:

<https://www.shc-24.com>

 **Invertex**
Drives.com