

ODV-3-560540-301N-MN

Optidrive Eco VFD Datasheet

37 kW (50 HP), 54 A, 500-600 V, 3PH
IP55 Variable Frequency Drive with TFT Display



Input Ratings

Supply Voltage	500-600 V
Input Phases	3
Supply Current Continuous	62.2 A
Supply Fuse or MCB (Type B)	80 A

Output Ratings

Motor Output Rating	37 kW (50 HP)
Output Voltage	0 – Supply Voltage
Output Current	54 A

Cable Information

Max Supply Cable Size	35 mm ² (0.05 sq in)
Max Motor Cable Size	35 mm ² (0.05 sq in)
Max Motor Cable Length	100 m (328 ft)

Factory Build Options

EMC Filter	No Internal EMC
Brake Transistor	No Brake Transistor
Enclosure	IP55
Display	TFT Display
PCB Coating	Standard

Drive Dimensions

Size	5
Height	540 mm (21.26 in)
Width	235 mm (9.25 in)
Depth	270 mm (10.63 in)
Weight	23 kg (50.71 lbs)
Fixings	4 x M8

Packaged Dimensions

Height	595 mm (23.43 in)
Width	350 mm (13.78 in)
Depth	375 mm (14.76 in)
Weight	25 kg (55.12 lbs)



SHC24

Buy this drive or get more
information:

<https://www.shc-24.com>

 **Invertetek**
Drives.com